



Sirius

EDITION 2017

BEÉPÍTHETŐ

Product name	Dim.	Motor	Model Identifier	Energy efficiency Class	Annual Energy Consumption	Fluid Dynamic Efficiency	Light Efficiency Class	Grease Filtering Efficiency Class	Weighted Sound Power Emission at maximum speed	Air Flow at intensive /boost setting	Lighting
				EEL	AEHood	FDE	LE	GFE	dB(A)	Qmax	W
SM 900	520	on-board	G900052PB1010657	B	58,1	B	A	B	70	604	2x2,1
SM 900	700	on-board	G900070PB1010657	B	54,9	B	A	B	70	654	2x2,1
SL 900	520	on-board	G900052PB1280657	A	46,6	A	A	B	70	762	2x2,1
SL 900	700	on-board	G900070PB1280657	A	46,9	A	A	B	70	773	2x2,1
SLT 900	520	on-board	G900052RC1280657	A	46,6	A	A	B	70	762	2x2,1
SLT 900	700	on-board	G900070RC1280657	A	46,9	A	A	B	70	773	2x2,1
SL 903-P	700	on-board	G903070PB1280541	A	55,2	A	A	B	69	700	4x2,1
SL 903-P-EM	700	SEM1	G903070PB1290541	B	58,1	B	A	B	65	630	4x2,1
SL 903-P-EM	700	SEM2	G903070PB1150541	C	80,2	C	A	B	66	630	4x2,1
SL 903-P	900	on-board	G903090PB1280541	A	50,9	A	A	B	69	705	4x2,1
SL 903-P-EM	900	SEM1	G903090PB1290541	B	58,5	B	A	B	65	624	4x2,1
SL 903-P-EM	900	SEM2	G903090PB1150541	C	81,1	C	A	B	66	632	4x2,1
SM 905	520	on-board	G905052PB1010624	B	58,1	B	A	B	70	604	2x2,1
SM 905	850	on-board	G905085PB1010624	B	54,9	B	A	B	70	654	2x2,1
SL 906-L	520	on-board	G906052PB1280152	A	46,5	A	A	A	71	680	1x6,5
SL 906-L	850	on-board	G906085PB1280253	A	49,0	A	B	A	71	743	1x10,5
SL 906-L	1000	on-board	G906100PB1280349	A	52,7	A	B	A	71	743	1x15,5
SL 907	520	on-board	G907052PB1281159	B	55,3	A	F	B	69	682	2x8
SL 907	700	on-board	G907070PB1281246	B	67,9	A	F	B	69	715	2x15
SL 909	856	on-board	G909086PB1282648	A	46,0	A	A	A	71	757	2x4
SL 909	1400	on-board	G909140PB1282648	A	49,2	A	A	A	71	768	4x4
SL 913	520	on-board	G913052PB1280127	A	58,8	A	D	B	69	668	1x6,5
SL 913	780	on-board	G913078PB1280227	A	52,2	A	E	B	69	721	1x10,5
SL 914	520	on-board	G914052PB1280529	A	57,1	A	A	B	69	668	2x2,1
SL 914	850	on-board	G914078PB1280524	A	55,7	A	A	B	69	721	2x2,1
SLTC 919	520	on-board	G919052TC1280166	A	46,5	A	A	A	71	680	1x6,5
SLTC 919	850	on-board	G919085TC1280267	A+	45,6	A	B	A	71	772	1x10,5

FALI

Product name	Dim.	Motor	Model Identifier	Energy efficiency Class	Annual Energy Consumption	Fluid Dynamic Efficiency	Light Efficiency Class	Grease Filtering Efficiency Class	Weighted Sound Power Emission at maximum speed	Air Flow at intensive /boost setting	Lighting
				EEL	AEHood	FDE	LE	GFE	dB(A)	Qmax	W
SL 31	600	on-board	P031060PB1280637	A	42,3	A	A	A	72	719	2x2,1
SL 31	900	on-board	P031090PB1280637	A	44,6	A	A	B	72	720	2x2,1
SL 31	1000	on-board	P031100PB1280637	A	44,6	A	A	B	72	720	2x2,1
SL 31	1200	on-board	P031120PB1280637	A	44,6	A	A	A	72	720	2x2,1
SL 31-EM	900	SEM1	P031090PB1290637	A	50,7	A	A	A	72	703	2x2,1
SL 31-EM	900	SEM2	P031090PB1150637	B	70,9	B	A	A	72	723	2x2,1
SL 50	600	on-board	P050060PB1280657	A	46,6	A	A	B	70	762	2x2,1
SLTR 75 (60)	600	on-board	P075060RB1010121	B	63,6	B	B	D	71	647	1x6,5
SLTR 75 (90)	900	on-board	P075090RB1280220	A+	45,6	A	B	D	71	757	1x10,5
SLTC 75 (60)	600	on-board	P075060TC1010121	B	63,6	B	B	D	71	647	1x6,5
SLTC 75 (90)	900	on-board	P075090TC1280220	A+	45,6	A	B	D	71	757	1x10,5
SLTC 86 80	800	on-board	P086080TC1010157	B	64,5	B	B	D	71	604	2x6,5
SL 89 55	550	on-board	P089055PB1280542	A	44,4	A	A	E	69	748	2x2,1
SL 89 80	800	on-board	P089080PB1280542	A	45,4	A	A	E	69	750	2x2,1
SLTC 90 55	550	on-board	P090055TC1280113	A	46,0	A	B	C	69	748	1x6,5
SLTC 91 80	800	on-board	P091080TC1280122	A	47,1	A	B	D	69	750	1x6,5
SLTC 92	900	on-board	P092090TC1280137	A	49,3	A	B	A	72	730	2x6,5
SL 92	900	on-board	P092090PB1280137	A	49,3	A	B	A	72	730	2x6,5
SLTC 93 60	600	on-board	P093060TC1280122	A	46,0	A	B	C	65	748	1x6,5
SLTC 93 90	800	on-board	P093080TC1280122	A	47,1	A	B	C	69	750	1x6,5
SLTC 94	800	on-board	P094080TC1280113	A	47,1	A	B	D	69	750	1x6,5
SLTC 95	670	on-board	P095067TC1280118	A	45,9	A	B	B	69	698	1x6,5
SLTC 97	900	on-board	P097090TC1280102	A	45,9	A	B	A	72	773	2x6,5
SLTC 103	700	on-board	P103070TC1280113	A	46,0	A	B	C	65	748	1x6,5
MO 207		on-board	P207040RC1282604	A	44,3	A	A	D	71	730	1x4
MO 208		on-board	P208036RC1282604	A	44,3	A	A	D	71	730	1x4

PULTBA ÉPÍTHETŐ

Product name	Dim.	Motor	Model Identifier	Energy efficiency Class	Annual Energy Consumption	Fluid Dynamic Efficiency	Light Efficiency Class	Grease Filtering Efficiency Class	Weighted Sound Power Emission at maximum speed	Air Flow at intensive /boost setting	Lighting
				EEL	AEHood	FDE	LE	GFE	dB(A)	Qmax	W
SDD2 INOX	580	on-board	D002058PB128XX07	A	45,9	A	n/a	E	69	636	no
SDD2_EM INOX	580	SEM1	D002058PB129XX07	A	44,6	B	n/a	E	66	595	no
SDD2_EM INOX	580	SEM2	D002058PB115XX07	C	83	C	n/a	E	68	577	no
SDD2_EM INOX	580	SEM8	D002058PB117XX07	C	101,1	C	n/a	E	70	622	no
SDD2_EM INOX	580	SEM10	D002058PB130XX07	B	52,2	C	n/a	E	67	478	no
SDD2 TC	580	on-board	D002058TC128XX07	A	45,9	A	n/a	E	69	636	no
SDD2_EM TC	580	SEM1	D002058TC129XX07	A	44,6	B	n/a	E	66	595	no
SDD2_EM TC	580	SEM2	D002058TC115XX07	C	83	C	n/a	E	68	577	no
SDD2_EM TC	580	SEM8	D002058TC117XX07	C	101,1	C	n/a	E	70	622	no
SDD2_EM TC	580	SEM10	D002058TC130XX07	B	52,2	C	n/a	E	67	478	no
SDD2-L INOX	580	on-board	D002058PB1281116	B	51,7	A	E	E	69	636	1x8
SDD2-L-EM INOX	580	SEM1	D002058PB1291116	B	50,5	B	E	E	66	595	1x8
SDD2-L-EM INOX	580	SEM2	D002058PB1151116	C	88,9	C	E	E	68	577	1x8
SDD2-L-EM INOX	580	SEM8	D002058PB1171116	C	106,9	C	E	E	70	622	1x8
SDD2-L-EM INOX	580	SEM10	D002058PB1301116	C	58,1	C	E	E	67	478	1x8
SDD2-L TC	580	on-board	D002058TC1281116	B	51,7	A	E	E	69	636	1x8
SDD2-L-EM TC	580	SEM1	D002058TC1291116	B	50,5	B	E	E	66	595	1x8
SDD2-L-EM TC	580	SEM2	D002058TC1151116	C	88,9	C	E	E	68	577	1x8
SDD2-L-EM TC	580	SEM8	D002058TC1171116	C	106,9	C	E	E	70	622	1x8
SDD2-L-EM TC	580	SEM10	D002058TC1301116	C	58,1	C	E	E	67	478	1x8
SDD2 INOX	875	on-board	D002088PB128XX05	A+	40,9	A	n/a	E	68	757	no
SDD2_EM INOX	875	SEM1	D002088PB129XX05	B	50,9	A	n/a	E	59	682	no
SDD2_EM INOX	875	SEM2	D002088PB115XX05	B	79,3	C	n/a	E	62	731	no
SDD2_EM INOX	875	SEM8	D002088PB117XX05	C	99	B	n/a	F	64	753	no
SDD2_EM INOX	875	SEM10	D002088PB130XX05	B	50,6	C	n/a	E	61	530	no
SDD2 TC	875	on-board	D002088TC128XX05	A+	40,9	A	n/a	E	68	757	no
SDD2_EM TC	875	SEM1	D002088TC129XX05	B	50,9	A	n/a	E	59	682	no
SDD2_EM TC	875	SEM2	D002088TC115XX05	B	79,3	C	n/a	E	62	731	no
SDD2_EM TC	875	SEM8	D002088TC117XX05	C	99	B	n/a	F	64	753	no
SDD2_EM TC	875	SEM10	D002088TC130XX05	B	50,6	C	n/a	E	61	530	no
SDD2-L INOX	875	on-board	D002088PB1281415	A	51,1	A	E	E	68	757	1x14
SDD2-L-EM INOX	875	SEM1	D002088PB1291415	B	61,1	A	E	E	59	682	1x14
SDD2-L-EM INOX	875	SEM2	D002088PB1151415	C	89,5	C	E	E	62	731	1x14
SDD2-L-EM INOX	875	SEM7 Ø150	D002088PB1161415	A	115,8	A	E	F	72	1142	1x14
SDD2-L-EM INOX	875	SEM7 Ø200	D002088PB1161415	A	119,4	A	E	F	74	1328	1x14
SDD2-L-EM INOX	875	SEM8	D002088PB1171415	C	109,2	B	E	F	64	753	1x14
SDD2-L-EM INOX	875	SEM10	D002088PB1301405	C	60,8	C	E	E	61	530	1x14
SDD2-L-EM INOX	875	SEM12	D002088PB1311405	B	71,7	A	E	E	68	668	1x14
SDD2-L TC	875	on-board	D002088TC1281415	A	51,1	A	E	E	68	757	1x14
SDD2-L-EM TC	875	SEM1	D002088TC1291415	B	61,1	A	E	E	59	682	1x14
SDD2-L-EM TC	875	SEM2	D002088TC1151415	C	89,5	C	E	E	62	731	1x14
SDD2-L-EM TC	875	SEM7 Ø150	D002088TC1161415	A	115,8	A	E	F	72	1142	1x14
SDD2-L-EM TC	875	SEM7 Ø200	D002088TC1161415	A	119,4	A	E	F	74	1328	1x14
SDD2-L-EM TC	875	SEM8	D002088TC1171415	C	109,2	B	E	F	64	753	1x14
SDD2-L-EM TC	875	SEM10	D002088TC1301405	C	60,8	C	E	E	61	530	1x14
SDD2-L-EM TC	875	SEM12	D002088TC1311405	B	71,7	A	E	E	68	668	1x14
SDD2-L INOX LED	875	on-board	D002088PB1282415	A	44,5	A	A	E	68	757	1x5
SDD2-L-EM INOX LED	875	SEM1	D002088PB1292415	B	54,5	A	A	E	59	682	1x5
SDD2-L-EM INOX LED	875	SEM2	D002088PB1152415	C	82,9	C	A	E	62	731	1x5
SDD2-L-EM INOX LED	875	SEM7 Ø150	D002088PB1162415	A+	109,2	A	A	F	72	1142	1x5
SDD2-L-EM INOX LED	875	SEM7 Ø200	D002088PB1162415	A+	112,9	A	A	F	74	1328	1x5
SDD2-L-EM INOX LED	875	SEM8	D002088PB1172415	C	102,6	B	A	F	64	753	1x5
SDD2-L-EM INOX LED	875	SEM10	D002088PB1302415	C	54,3	C	A	E	61	530	1x5
SDD2-L-EM INOX LED	875	SEM12	D002088PB1312415	B	65,2	A	A	E	68	668	1x5
SDD2-L TC LED	875	on-board	D002088TC1282415	A	44,5	A	A	E	68	757	1x5

PULTBA ÉPÍTHETŐ

Product name	Dim.	Motor	Model Identifier	EEI	AEChood	FDE	LE	GFE	dB(A)	Qmax	W
SDD2-L-EM TC LED	875	SEM1	D002088TC1292415	B	54,5	A	A	E	59	682	1x5
SDD2-L-EM TC LED	875	SEM2	D002088TC1152415	C	82,9	C	A	E	62	731	1x5
SDD2-L-EM TC LED	875	SEM7 Ø150	D002088TC1162415	A+	109,2	A	A	F	72	1142	1x5
SDD2-L-EM TC LED	875	SEM7 Ø200	D002088TC1162415	A+	112,9	A	A	F	74	1328	1x5
SDD2-L-EM TC LED	875	SEM8	D002088TC1172415	C	102,6	B	A	F	64	753	1x5
SDD2-L-EM TC LED	875	SEM10	D002088TC1302415	C	54,3	C	A	E	61	530	1x5
SDD2-L-EM TC LED	875	SEM12	D002088TC1312415	B	65,2	A	A	E	68	668	1x5
SDD2-L INOX	1175	on-board	D002118PB1281317	B	60,7	A	F	E	65	791	1x21
SDD2-L-EM INOX	1175	SEM1	D002118PB1291317	B	58,7	A	F	E	55	736	1x21
SDD2-L-EM INOX	1175	SEM2	D002118PB1151317	C	99,4	B	F	E	57	738	1x21
SDD2-L-EM INOX	1175	SEM8	D002118PB1171317	C	107,3	B	F	F	60	807	1x21
SDD2-L-EM INOX	1175	SEM10	D002118PB1301317	C	67,1	C	F	E	59	559	1x21
SDD2-L TC	1175	on-board	D002118TC1281317	B	60,7	A	F	E	65	791	1x21
SDD2-L-EM TC	1175	SEM1	D002118TC1291317	B	58,7	A	F	E	55	736	1x21
SDD2-L-EM TC	1175	SEM2	D002118TC1151317	C	99,4	B	F	E	57	738	1x21
SDD2-L-EM TC	1175	SEM8	D002118TC1171317	C	107,3	B	F	F	60	807	1x21
SDD2-L-EM TC	1175	SEM10	D002118TC1301317	C	67,1	C	F	E	59	559	1x21
SDD3_EM_TC	520	on-board	D003052TC128XX07	A	45,9	A	n/a	E	69	636	no
SDD3_EM_TC	520	SEM1	D003052TC129XX07	A	44,6	B	n/a	E	66	595	no
SDD3_EM_TC	520	SEM2	D003052TC115XX07	C	83	C	n/a	E	68	577	no
SDD3_EM_TC	520	SEM8	D003052TC117XX07	C	101,1	C	n/a	E	70	622	no
SDD3_EM_TC	520	SEM10	D003052TC130XX07	B	52,2	C	n/a	E	67	478	no
SDD4_880TC	880	on-board	D004088TC1281415	A	51,1	A	E	E	68	757	1x14
SDD4_EM_880TC	880	SEM1	D004088TC1291415	B	61,1	A	E	E	59	682	1x14
SDD4_EM_880TC	880	SEM2	D004088TC1151415	C	89,5	C	E	E	62	731	1x14
SDD4_EM_880TC	880	SEM8	D004088TC1171415	C	109,2	B	E	F	64	753	1x14
SDD4_EM_880TC	880	SEM10	D004088TC1301415	C	60,8	C	E	E	61	530	1x14
S-DD11 X	810	on-board	D011088PB1282219	B	59,6	B	F	E	68	681	2x3,9
S-DD11 EM X	810	SEM1	D011088PB1292219	B	55,4	B	F	E	59	633	2x3,9
S-DD11 EM X	810	SEM2	D011088PB1152219	C	80,2	C	F	E	62	639	2x3,9
S-DD11 EM X	810	SEM10	D011088PB1302219	C	57,9	C	F	E	70	478	2x3,9
S-DD11 EM X	810	SEM12	D011088PB1312219	C	79,7	C	F	E	71	576	2x3,9
S-DD12 TC	870	on-board	D012088TC1282339	A	49,6	A	E	E	68	750	1x12
S-DD12 EM TC	870	SEM1	D012088TC1292339	B	51,7	A	E	E	59	687	1x12
S-DD12 EM TC	870	SEM2	D012088TC1152339	B	79,4	B	E	E	62	718	1x12
S-DD12 EM TC	870	SEM8	D012088TC1172339	B	97,9	B	E	F	64	816	1x12
S-DD12 EM TC	870	SEM10	D012088TC1302339	C	57,2	C	E	E	61	530	1x12
S-DD13	880	on-board	D013088TC1283163	A	50,8	A	C	C	68	690	1x9,5
S-DD13 EM	880	SEM1	D013088TC1293163	A	48,7	A	C	C	59	660	1x9,5
S-DD13 EM	880	SEM2	D013088TC1153163	B	75,2	B	C	C	62	665	1x9,5
S-DD13 EM	880	SEM8	D013088TC1173163	C	109,4	C	C	C	64	775	1x9,5
S-DD13 EM	880	SEM10	D013088TC1303163	C	65,7	D	C	C	61	525	1x9,5
S-DD16 EM	845	SEM1	D016085TC129XX61	A	47,5	B	n/a	C	66	600	no
S-DD16 EM	845	SEM2	D016085TC115XX61	B	73,6	C	n/a	D	68	582	no
S-DD16 EM	845	SEM10	D016085TC130XX61	B	52,1	C	n/a	C	70	484	no
S-DD16 EM	845	SEM12	D016085TC131XX61	B	73,6	C	n/a	C	71	577	no
S-DD16 EM	845	SEM13	D016085TC125XX61	C	87,2	C	n/a	C	66	645	no
S-DD17 EM	520	SEM1	D017052TC129XX69	A	47,8	A	n/a	C	66	618	no
S-DD17 EM	520	SEM2	D017052TC115XX69	B	73,1	C	n/a	D	68	597	no
S-DD17 EM	520	SEM10	D017052TC130XX69	C	59,7	D	n/a	C	70	493	no
S-DD17 EM	520	SEM12	D017052TC131XX69	B	67,5	B	n/a	C	71	642	no
S-DD17 EM	520	SEM13	D017052TC125XX69	C	87,2	C	n/a	C	66	645	no
UPRIGHT BUILT-IN	800	on-board	U001087PB1280262	A	48,5	A	B	F	68	755	1x10,5
UPRIGHT-EM BUILT-IN	800	SEM1	U001087PB1290262	A	55	A	B	F	59	685	1x10,5
UPRIGHT-EM BUILT-IN	800	SEM2	U001087PB1150262	C	91	C	B	F	62	763	1x10,5

E E ETBE ÉPÍTHETŐ

Product name	Dim.	Motor	Model Identifier	EEI	AEChood	FDE	LE	GFE	dB(A)	Qmax	W
SLT951 EM		SEM1	C951110RC1291037	C	89	A	F	F	57	706	4x16
SLT951 EM		SEM2	C951110RC1151037	C	129,5	B	F	F	61	773	4x16
SLT951 EM		SEM8	C951110RC1171037	C	138,2	B	F	F	64	869	4x16
SLT958		on-board	C958090RC1280137	A	54,8	A	B	F	67	758	2X6,5
SLT958 EM		SEM1	C958090RC1290137	B	63,1	B	B	F	55	670	2X6,5
SLT958 EM		SEM2	C958090RC1150137	B	73,4	A	B	F	59	790	2X6,5
SLT958 EM		SEM8	C958090RC1170137	B	96,9	B	B	F	62	900	2X6,5
SLT958 W		on-board	C958090RC1280137	A	54,8	A	B	F	67	758	2X6,5
SLT958 EM W		SEM1	C958090RC1290137	B	63,1	B	B	F	55	670	2X6,5
SLT958 EM W		SEM2	C958090RC1150137	B	73,4	A	B	F	59	790	2X6,5
SLT958 EM W		SEM8	C958090RC1170137	B	96,9	B	B	F	62	900	2X6,5
SLT960		on-board	C960110RC1280435	B	69,1	A	E	F	66	753	2X18,5
SLT960 EM		SEM1	C960110RC1290435	B	83,8	B	E	F	65	681	2X18,5
SLT960 EM		SEM2	C960110RC1150435	C	97,8	B	E	F	71	736	2X18,5
SLT960 EM		SEM8	C960110RC1170435	C	120,1	B	E	F	70	855	2X18,5
SLT962		on-board	C962090RC1241940	C	63,3	C	D	F	61	604	1x20
SLT962 EM		SEM1	C962090RC1291940	B	74,6	B	D	F	65	602	1x20
SLT962 EM		SEM2	C962090RC1151940	C	101,8	C	D	F	71	610	1x20
SLT962 EM		SEM8	C962090RC1171940	B	104	B	D	F	70	832	1x20
SLT963		on-board	C963095RC1240324	C	75,9	C	B	F	69	579	2x15,5
SLT963 EM		SEM1	C963095RC1290324	B	81,7	B	B	F	65	690	2x15,5
SLT963 EM		SEM2	C963095RC1150324	C	92,1	B	B	F	71	733	2x15,5
SLT963 EM		SEM8	C963095RC1170324	C	112	B	B	F	70	832	2x15,5
SLT965		on-board	C965110RC1270460	B	87,6	B	E	F	70	707	2X18,5
SLT965		on-board	C965110RC1240460	C	79,3	C	E	F	66	588	2X18,5
SLT965 EM		SEM1	C965110RC1290460	B	72	A	E	F	65	687	2X18,5
SLT965 EM		SEM2	C965110RC1150460	C	98,1	B	E	F	71	695	2X18,5
SLT965 EM		SEM8	C965110RC1170460	C	120,1	B	E	F	70	855	2X18,5
SLT966		on-board	C966100RC1243268	B	56,4	C	C	F	63	615	2x5
SLT966		on-board	C966100RC1273268	B	68,6	B	C	F	68	757	2x5
SLT966 EM		SEM1	C966100RC1293268	A	51,3	A	C	F	71	675	2x5
SLT966 EM		SEM2	C966100RC1153268	B	79,2	B	C	F	71	691	2x5
SLT966 EM		SEM8	C966100RC1173268	C	111,1	C	C	F	69	790	2x5
SLT967		on-board	C967100RC1242565	C	71,8	C	0	F	63	615	2x15,5
SLT967		on-board	C967100RC1272565	B	84	B	0	F	68	757	2x15,5
SLT967 EM		SEM1	C967100RC1292565	B	66,6	A	0	F	71	675	2x15,5
SLT967 EM		SEM2	C967100RC1152565	C	94,5	B	0	F	71	691	2x15,5
SLT967 EM		SEM8	C967100RC1172565	C	126,4	C	0	F	69	790	2x15,5

I ET

Product name	Dim.	Motor	Model Identifier	EEI	AEChood	FDE	LE	GFE	dB(A)	Qmax	W
SIL 5	900	on-board	I005090PB1280637	A	47,7	A	A	A	70	720	4x2,10
SIL 5	1200	on-board	I005120PB1280637	A	47,7	A	A	A	70	720	4x2,10
SIL-EM 5	900	SEM1	I005090PB1290637	A	53,8	A	A	A	70	703	4x2,10
SIL-EM 5	900	SEM2	I005090PB1150637	B	74,0	B	A	A	70	723	4x2,10
SIL 24	900	on-board	I024090PB1280137	A	49,3	A	B	A	70	730	2x6,5
SIL 24 TC	900	on-board	I024090PB1280137	A	49,3	A	B	A	70	730	2x6,5
MO 404		on-board	I404036RC1282604	A	44,3	A	A	D	71	730	1x4
MO 405		on-board	I405040RC1282604	A	44,3	A	A	D	71	730	1x4
MO 406		on-board	I406040RC1280857	B	70,6	A	D	D	71	730	1x40